PHILIPS

BVP182 LED80/NW 50W WB CN

911401905011



Tempo HE, 8000 lm, 50 W, 840 neutral white, Fixed Output, Safety class I

The Tempo HE builds on the iconic design of the previous-generation BVP17X, preserving its elegant, minimalist aesthetic while marking a complete evolution in performance. Engineered as a fully new generation luminaire, it integrates high-efficiency LED chips, an advanced optical system, an efficient heat sink, and a high-performance driver into a compact, all-in-one housing—streamlining structure and simplifying installation. The Tempo HE series achieves outstanding energy savings and delivers bright, comfortable illumination, combined with enhanced durability and an extended service life.

Warnings and Safety

- Suitable for general outdoor application, NOT recommended for very severe conditions (marine areas, beaches, deserts or any harsh environment)

General Information

Gear	-
Driver included	Yes
Light source engine type	LED
Value ladder	Performance

Light Technical

Luminous Flux	8,000 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	160 lm/W
Color rendering index (CRI)	80
Beam angle of light source	- degree(s)
Light source color	840 neutral white

Optic type	-
Effective projected area	0.041 m^2

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	25 A
Power Consumption	50 W
Power Factor (Fraction)	0.95
Connection	Flying leads/wires
Cable	Cable 0.7 m without plug
Number of products on MCB of 16 A type B	7
Protection class IEC	Safety class I

Controls and Dimming

Dimmable	No
Control interface	Fixed Output

Mechanical and Housing

Housing Material	Aluminum die cast
Optic material	Polycarbonate
Optical cover material	-
Housing Color	RAL 7043
Optical cover finish	-
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	-
Net Weight (Piece)	1.500 kg

Approval and Application

Glow-wire test	-
Flammability mark	-
CE mark	No
ENEC mark	-
EU RoHS compliant	Yes
Ambient temperature range	-40 to +50 °C


Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	BVP182 LED80/NW 50W WB CN
Full product name	BVP182 LED80/NW 50W WB CN
Order code	911401905011
Material Nr. (12NC)	911401905011
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6922341986703
Numerator - Packs per outer box	6
EAN/UPC - Case	6922341987069

Dimensional drawing



© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.